

closures



VENTED CLOSURE ROLL

Specially formulated coated polyester has been manufactured from recycled material and is recyclable. Won't absorb moisture, which can freeze and block all ventilation. Vented material will provide maximum air flow, yet prevent wind driven rain when compressed. Unique doubled beaded adhesive for a durable holding strength. Available in 20' rolls



UNIVERSAL CLOSURE

The material is a flexible semi-closed cell material that is used for filling voids & other openings between metal panels. This closure works well for filling gaps in a panel cut for a valley or hip. They have pre-applied adhesive. Standard length is 25'



BUTYL

A 100% solids, asbestos free butyl tape sealant in roll form. Applications include metal roof end laps, side laps, vents, gutters, pipe flashings, skylights. Service temperature range is -40 Degrees F- +180 Degrees F. Material will not become brittle or crack. Available in 3/32" x 3/8" x 45'



INSIDE/OUTSIDE PANEL CLOSURE

Designed to close gaps in roof & sidewall applications. Material is pre-cut to conform to metal panel configurations. Applications include closing the openings at the ridge (peak of the building) or at the eave (gutter-line of a building). 1.8 lb. Density polyethylene foam is designed to withstand harsh weather elements including moisture & ultraviolet rays.



INSIDE/OUTSIDE PANEL CLOSURE

Optional pre-applied adhesive helps to keep closure in place before the roof panel is fastened. Interlocking dovetails provide a secure end-to-end fit, eliminating any potential gaps.

Available in PBR and AG profiles